

Pneumatic Separator



D-106



D-147



D-130

	36"	36"	48"	54"	48"	54"	60"	72"
Production (lb/hr)	2000	3000	3500	4000	11500	13000	15000	19500
Air Capacity (cfm)	3500	4600	5700	6800	10000	11000	12000	14000
Staple Length	<=3"	<8"	<8"	<8"	<8"	<8"	<8"	<8"
Horsepower	1	2	2	2	2/2	2/2	2/2	2/2
Weight (lb)	575	900	1000	1100	1500	1800	2000	2400
Height (in)	37	47	47	47	71	71	71	71
Depth (in)	24	30	30	30	45	45	45	45
Inlet Height (in)	37	47	47	47	64-1/2	64-1/2	64-1/2	64-1/2
Outlet Height (in)	20-1/2	21	21	21	42-3/4	42-3/4	42-3/4	42-3/4

Machines shown are standard designs. Optional configurations are available per customer request. Special options are available and include complete electrical controls, "CE" compliance and metric construction, custom painting, supports stands, inlet & outlet transitions, outlet diverters with pneumatic cylinder, special Impreglon coatings on the curved screen and special wiper blade material. Ibis also offers other types of scrap, trim and cull collectors as well as rotary drum filters and fans to provide a complete engineered process system.